

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/068681 A1

(51) International Patent Classification⁷: **H02K 35/02**,
B62J 6/06

(21) International Application Number:
PCT/GB2003/005100

(22) International Filing Date:
24 November 2003 (24.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0301870.2 27 January 2003 (27.01.2003) GB

CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant and
(72) Inventor: GANG, QIN [GB/GB]; 63 GRAYS INN ROAD, LONDON, Greater London WC1X 8TL (GB).

Published:
— with international search report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A TUMBLING MAGNET ELECTRICITY GENERATING SYSTEM



(52) Abstract: The first magnet (9) is set free to tumble within a tumbling chamber (10). A coil (11) wound around the outer surface of the tumbling chamber (10). The two ends of the coil (11) are connected to the terminals of an LED (light emitting diode) (3). There is an arbitrary, relative motion between the first magnet (9) and the second magnet (2). The magnets depicted with dotted lines represent alternative, relative motions of the second magnet (2) with respect to the first magnet (9). As the first magnet (9) and the second magnet (2) pass close to one another, the mutual interaction of the magnetic fields is sufficient to cause the first magnet (9) to tumble in the tumbling chamber (10). As the first magnet (9) tumbles in the tumbling chamber (10), a varying magnetic field is effected through the coil (11) and a corresponding electric current flows through the coil (11) thus illuminating the LED 3.

WIPO 2004/068681 A1

A Tumbling Magnet Electricity Generating System

This invention relates to an electricity generating system in which electromagnetic induction is effected by way of a permanent magnet tumbling (caused by another magnet) in a coil, and produces a varying magnetic field flux through the coil, such that a corresponding potential difference is formed across opposite ends of the coil (generating electricity). It is applicable to illumination of a bicycle for safety purposes, or run other electric appliances.

A voltage is set up across opposite ends of a coil in a magnetic field whenever the magnetic field changes. This effect is called electromagnetic induction. If the coil forms part of a closed circuit the induced voltage causes a current to flow in the circuit. The majority of known electricity generating systems are based on the phenomenon of electromagnetic induction.

According to an embodiment of the invention there is provided a tumbling magnet electricity generating system for supplying electricity to at least one electrical device, comprising a tumbling chamber, a first magnet arranged within the tumbling chamber, a second magnet arranged externally to the tumbling chamber, and a coil looped around the tumbling chamber, adapted such that the tumbling chamber is of sufficient dimensions to allow the first magnet to freely tumble, and such that on proximal relative motion of said first and second magnets, causes the first magnet to tumble in the tumbling chamber, generating a varying magnetic flux through the coil such that a corresponding potential difference is formed across opposite ends of the coil. It generates electricity to run an electric appliance, e.g. an LED (Light Emitting Diode).

A specific embodiment of the invention will now be described by way of example and with reference to the accompanying drawings in which:

Fig. 1 shows a cross-sectional view of an electricity generating system. The first magnet 9 is set free to tumble within a tumbling chamber 10 around which a coil 11 is looped. The two ends of the coil 11 are connected to the terminals of an LED (light emitting diode) 3. There may be some arbitrary, relative motion between the first magnet 9 and the second magnet 2. The magnets depicted with dotted lines represent alternative, relative motions of the second magnet 2 with respect to the first magnet 9. As the first magnet 9 and the second magnet 2 pass close to one another, the mutual interaction of the magnetic fields is sufficient to cause the first magnet 9 to tumble in

the tumbling chamber 10. As the first magnet 9 tumbles in the tumbling chamber 10, a varying magnetic field flux is effected through the coil 11 and a corresponding electric current flows through the coil 11 thus illuminating the LED 3.

Fig. 2 shows an electricity generating unit 4 attached supportedly on a front wheel fork 1 of a bicycle. The support 5 is made of non-magnetic materials. The second magnet 2 is fixedly attached to the spokes 6 of the bicycle wheel 7. As the wheel rotates, the second magnet 2 will pass close to the electricity generating unit 4, containing the first magnet 9, once per revolution of the bicycle wheel 7 and will generate electricity as described above.

Fig. 3 represents a cross-sectioned front view of an electricity generating system. The electricity generating unit 4 is made from a coil 11 of insulated copper wire wound around a tumbling chamber 10 which is of non-magnetic, synthetic materials. The two coil 11 ends are connected to the terminals of an LED 3. The first magnet 9 is a disc shaped permanent magnet and is enclosed within the tumbling chamber 10. The tumbling chamber 10 is of sufficient dimensions to allow the first magnet 9 to tumble freely. The second magnet 2, a permanent magnet is fixedly attached to the spokes 6 of the bicycle wheel 7 by a fixing member 8. As the bicycle wheel 7 rotates, the second magnet 2 passes close to the first magnet 9 whereupon the interaction of their magnetic fields will cause the first magnet 9 to tumble in the tumbling chamber 10. As the first magnet 9 tumbles, it produces a rapidly varying magnetic field that induces an electric current to flow through the coil 11 and to light the LED 3.

Figs. 4-6 are viewed perpendicular to the plane of rotation of a bicycle wheel 7 and include cross-sectional views of the tumbling chamber 10. Figs. 4-6 illustrate the operation of the electricity generating system during a revolution of a bicycle wheel.

Fig. 4 shows the second magnet 2 approaching the first magnet 9. The interaction of their magnetic fields will not be strong enough to cause the first magnet 9 to tumble in the tumbling chamber 10. No electric voltage will be generated in the coil 11. The LED 3 is off.

Fig. 5 shows the second magnet 2 passing proximal to the first magnet 9 as the bicycle wheel 7 rotates. When the distance between first magnet 9 and the second magnet 2 is at a minimum, the magnetic interaction will be causing the first magnet 9 to tumble in the tumbling chamber 10. As the first magnet 9 tumbles, a rapidly varying magnetic field flux induces an electric current to flow in the coil 11 and thus causes the LED 3 to be illuminated.

Fig. 6 shows the second magnet 2 having moved passed the first magnet 9. The interaction of their magnetic fields will not be strong enough to cause the first magnet 9 to tumble in the tumbling chamber 10. No electric voltage will be generated in the coil 11. The LED 3 is off.

Accordingly there will be a part of each revolution of the wheel 7 during which the LED 3 will be at least flickeringly illuminated. As the rotation speed of the wheel increases, the frequency of at least flickeringly illuminated periods increases proportionally.

CLAIMS

1. A tumbling magnet electricity generating system for supplying electricity to at least one electrical device, comprising a tumbling chamber (10), a first magnet (9) arranged within the tumbling chamber (10), a second magnet (2) arranged externally to the tumbling chamber (10), and a coil (11) looped around the tumbling chamber (10), adapted such that the tumbling chamber (10) is of sufficient dimensions to allow the first magnet (9) to freely tumble, and such that on proximal relative motion of said first and second magnets, the mutual interaction of the magnetic fields is sufficient to cause the first magnet (9) to tumble in the tumbling chamber (10), generating a varying magnetic flux through the coil (11) such that a corresponding potential difference is formed across opposite ends of the coil (11), generating electricity to run an electric appliance.
2. A tumbling magnet electricity generating system as claimed in claim 1, wherein the tumbling chamber (10) is substantially of non-magnetic material.
3. A tumbling magnet electricity generating system as claimed in claim 1 wherein the coil (11) comprises an insulated copper wire wound around the outer surface of the tumbling chamber (10), the opposite ends of the coil (11) being electrically connected to terminals of an electric appliance.
4. A tumbling magnet electricity generating system as claimed in claim 1 wherein the first magnet (9) is substantially of a known geometric shape.
5. A tumbling magnet electricity generating system as claimed in one of claims 1 and 2, wherein the tumbling chamber (10) is substantially of a known geometric shape.
6. A bicycle comprising the tumbling magnet electricity generating system of claim 1 for providing illumination.
7. A tumbling magnet electricity generating system as claimed in claim 1 or 6, wherein the second magnet (2) is fixedly attached to a wheel of a bicycle.
8. A tumbling magnet electricity generating system as claimed in claim 1 or 6 wherein the electricity generating unit containing the first magnet (9) is fixedly attached stationary relative to and non-rotate relative to a part of a bicycle frame by a supporting member.

9. A tumbling magnet electricity generating system as claimed in any one of claims 1, 6, 7 and 8, wherein on rotation of a bicycle wheel the second magnet (2) passes proximal to the first magnet (9) once during each rotation of said wheel.

10. A safety signal generator for a bicycle comprising a tumbling magnet electricity generating system of any one of claims 1, 6, 7, 8, 9 and 10, and at least one light emitting diode electrically connected to the coil (11) of the tumbling magnet electricity generating system wherein a rotation of the first magnet (9) causes a varying electric current to flow through the coil (11) and illuminate the light emitting diode.






FIG 1






FIG 4




FIG 5




FIG 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/05100

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H02K35/02 B62J6/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H02K B62J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01/33700 A (RELIGHT) 10 May 2001 (2001-05-10) abstract page 2, lines 9-32 page 6, line 18 - page 7, line 17 page 8, lines 1-18 page 9, lines 16-19; figures 1,2,4,7	1,6-10
A	WO 02/103881 A (NEULANDS TECHNOLOGY LIMITED) 27 December 2002 (2002-12-27) abstract page 5, lines 6-10 page 6, line 8 - page 7, line 14; figures 1-4 ----- -/-	1-5



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the International filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the International search

9 March 2004

Date of mailing of the international search report

16/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Beitner, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/05100

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 584 561 A (LAHOS) 17 December 1996 (1996-12-17) abstract column 2, line 55 - column 3, line 23; figures 1-3 -----	1,6-10
A	US 5 606 210 A (LIN) 25 February 1997 (1997-02-25) abstract column 2, lines 17-49 column 3, lines 1-25; figures 1-3,5,5A -----	1-5
A	FR 2 407 599 A (JUILLET HUBERT) 25 May 1979 (1979-05-25) the whole document -----	1-5

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 03/05100

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 0133700	A	10-05-2001	AU	1130801 A		14-05-2001
			WO	0133700 A1		10-05-2001
WO 02103881	A	27-12-2002	WO	02103881 A2		27-12-2002
US 5584561	A	17-12-1996	CA	2130852 A1		26-02-1996
			AU	1379295 A		14-03-1996
			WO	9605999 A1		29-02-1996
US 5606210	A	25-02-1997	NONE			
FR 2407599	A	25-05-1979	FR	2407599 A1		25-05-1979